

Compressed Air Filters

Introducing our NEW aluminium range of compressed air filters
A complete range of in-line filter housings including auto drain valves and differential pressure indicators.



0

TECHNICAL DATA					HOUSING DIMENSIONS (mm)				
Filter Model	Connection Size	Flow Rate (m3/h)	Max. Working Pressure	Element Model	A	B	C	D	E
G50	3/8"	50	16	M50	96	20	237	110	22
G100	1/2"	100	16	M100	96	20	237	150	22
G150	3/4"	150	16	M150	117	34	375	190	56
G200	3/4"	200	16	M200	117	34	375	250	56
G250	1"	250	16	M250	117	34	465	300	56
G300	1 1/4"	300	16	M300	117	34	465	350	56
G500	1 1/4"	500	16	M500	117	34	530	380	56
G600	1 1/2"	600	16	M600	117	34	530	425	56
G851	2"	851	16	M851	170	64	722	480	56
G1210	2"	1210	16	M1210	170	64	722	550	56
G1510	2 1/2"	1510	12	M1510	235	72	760	430	56
G1810	3"	1810	12	M1810	235	72	760	550	56
G2210	3"	2210	12	M2210	235	72	760	600	56

SPECIFICATIONS	PRE-FILTER	GENERAL PURPOSE	OIL REMOVAL
Grade	P	X	Y
Particle removal (Micron)	5	1	0.01
Max oil carryover at 21 C (mg/m3)	5	0.5	0.01
Max working temperature (deg C)	80	80	80
Initial pressure drop (mbar)	40	80	100
Element colour code	Green	Blue	Red

